

Golden period of particle physics



Detector of Today



A history: Slide shown in XIth DAE Symposium @Santiniketan (1994)





Fig. 1.4: Neutron fluence and dose in CMS. The numbers in the figure are the fluence in units of 10^{13} n/cm². Numbers in bold are the dose in Mrads. These numbers are given for an integrated luminosity of $L = 10^{42}$ cm⁻², corresponding to 10 years of running at design luminosity.

LHC 8-sourcer 1:17-4 3 66 0.04 rad (s ~56 rad (s 1:32 MeV) 66 MSGC →Silicon strip CeF_3 → PbWO₄


CMS and **ATLAS** Tracking Detector



CMS members hold the OPAL Vertex Detector in front of the CMS Silicon Strip Detector

L3 tracker had 74K channels, whereas CMS is having 76M channels (increases by three order)

Bunch spacing: LEP to LHC: 23µs to 25ns



Same is true for $KGF \rightarrow INO$

straw tubes (Xe), 4×10^5 channels e/π

 $\sigma/p_{T} \sim 5x10^{-4} p_{T} \oplus 0.01$

separation


Physics goal of CMS
Don't know what will we find at the LHC!


ATLAS and CMS are "general purpose" detectors – they need to be designed to be able to detect anything!

We believe that the Higgs boson, and/or Supersymmetric (SUSY) particles exist, and the LHC will provide collisions energetic enough to create them

But we cannot see Higgs/SUSY particles directly as they either decay to lighter (stable) particles or cannot be seen with any known detector


We have to design our detector to look for the stable particles and signs of "invisible" particles.....






Fermilab

Physics processes at LHC



Interesting physics processes are 10^{-10} - 10^{-9} times smaller than inelastic pp interaction rate \rightarrow Searching for a needle in a hay stack

LHC machine



Energy GeV

Luminosity

Beams


RF & Future Expt.	Low ß (pp) High Luminosity CMS	Dump
Cleaning Cleaning Octavity	Cant 5 Octant 5	Octant 7
ALICE Injection	Octant 1	Low B (B physics)

LHC P	p 14000 10 ³² cm ² s ⁻¹ 1,312,000 10 ²⁷
Beam Energy	
Peak Luminosity (L)	$10^{34} \text{ cm}^{-2} \text{s}^{-1}$
σ_{pp} ND (+ D) †	70 mb (+ 10 mb)
ND events at peak \mathcal{L}	$7 \times 10^8 \text{ s}^{-1}$
Protons / beam at start of fill	3×10^{14}
Fills per day × duration †	$1 \times 20 \text{h}$ or $2 \times 8 \text{h}$
Operation days per year $(pp)^{\dagger}$	3 × 60
L (24h average) †	$5 \times 10^{33} \text{cm}^{-2} \text{s}^{-1}$
$\int \mathcal{L} dt$ (per year) †	$0.75 \times 10^5 \text{ pb}^{-1}$
ND events (24h average) †	$3.5 \times 10^8 \text{ s}^{-1}$
Number of ND events per year †	5.5×10^{15}
\mathcal{L} (years 1–4 in % of max.) †	10, 33, 67, 100
Protons lost in experiments/beam †	3×10^{13} / day
Protons lost in scrapers/beam [†]	9 × 10 ¹³ / day
Protons lost around ring / beam †	2×10^{13} / day
Protons dumped/beam per day †‡	46×10^{13} , 18×10^{13}

[†]Preliminary assumption.


[‡]For 8h and 20h fills.


Collisions at the Large Hadron Collider



Basic concepts of HEP detector

- Heavy particles decay to low mass particles
- Stable particles are detected in the detector
- Stable particles : e^{\pm} , γ , ρ , ρ -bar, $\underline{K^{\pm}}$, $\underline{\pi^{\pm}}$, $\underline{K_L}$, \underline{n} , \underline{n} -bar, $\underline{\mu^{\pm}}$, ν , ν -bar
- Design detector which can detect all these stable particles
- Layers of subdetectors to detect different particle in different detector layer
- Most interacting particles are detected in the innermost layer and less interacting one in the





• Track length in beam pipe Beam pipe design

$$\ell = \frac{t}{\sin(2\arctan e^{-\eta})} \approx \frac{t}{2e^{-\eta}}$$

- For $\eta=5.3$ and t=2mm $\Rightarrow \ell=20$ cm
- High cost, handling problem and toxicity reduced Be beam pipe upto ~ ± 75cm
- Beyond η=2.5, there are no strong constraints from CMS performance
- Al has problem with welding, NEGcoating (upto ± 1.98 m)

Remaining part is made of Stainless steel


2×10⁶

Cyl. pipe

Con. pipe


TDR pipe

Charged hadron flux at R=15-30cm



Shielding of hadronic beam background

- Low energy neutron shielding using hydrogenous material
- E>10 MeV, cross section is small (1/v), heavier material provide better shielding but inelastic interaction with several neutrons in the final state, good choice is medium mass nuclei, good materials are cadmium [(A(n,n)A*] and boron[(n,α)]
 - At high energies boron has inelastic interaction, which increase the neutron flux
 - Cadmium produces numerous energetic capture gammas



The general solution to shield radiation in accelerator environments:

To reduce the flux of high energy particle with dense but medium A material, e.g. iron, placed close to the source. Then to slow down neutrons with hydrogenated materials and to capture them either in the hydrogen or with boron or cadmium. Finally the photons can be suppressed with a layer of lead 12.

Detecting signature of the Higgs/SUSY particles


- If Higgs mass is around 115-130 GeV, the easiest way to detect it is via its decay to two photons
 - Need an excellent electromagnetic calorimeter ECAL (for 4-moneta of photons)
 - Need excellent tracker to identify the primary interaction vertex
- If the Higgs is heavier, it may be seen via its decay to electrons and/or muons
 - Need an excellent ECAL, Need excellent muon chambers (for muon identification and momentum measurement) and central tracking (for momentum measurement)
 - Many SUSY particles decay to hadronic jets (many charged and neutral particles in a tight bunch)
 - Need good calorimeters hadronic (HCAL) and ECAL
 - SUSY decays also lead to the production of the "lightest supersymmetric particle" (LSP), which is invisible in any known detector
 - Need excellent calorimetry coverage in order to detect "missing" energy

Requirements:


- A good and redundant muon system
- The best possible electromagnetic calorimeter
- A high quality central tracking
- A hadronic calorimeter that has good energy resolution and that is as hermetic as possible
- Affordable! (~500 MCHF)

CMS tracker


• Design to reconstruct high P_T muons, isolated electrons and hadrons with high momentum resolution and an efficiency better than 98% in the range $|\eta| < 2.5$ along with the identification of detached vertex (efficiency to detect



• Precise position measurement, robustness in high density of particle flux/rate (decreasing as $1/r^2$). 4T magnetic field removes low P_T charge particles. Dose (Gy) Neutrons (cm²) Ch. Hadrons (cm²)



CMS tracker



Type inversion due to high radiation dose ⇒*p*-substrate


Pixels: 150 μm × 150μm

Strip pitch: 80 to 205 µm

Outer region: higher noise due to "long" strip is compensated by larger signal in thick (500µm) sensor

Total readout channel: 9.6 M

Operating at -10°C



1.6

1.7

1.8

1.9

2.1

2.2


2.3 2.4 2.5

Design of CMS silicon strip/pixel detector

- Barrel detector uses the principle of Lorentz angle to improve resolution
- Endcap detector are put a paddle/blade shape disk to have a

Total Area: 0.78+0.28 m²


66 Million Pixels





ΤU

Double sided (DS) module

- DS modules are two single sided modules literally glued back-to-back
- DS modules eventually provide 2D hit information.
- Large angle has more ghost hit, whereas small angle has poorer position information.








Occupancy/granularity


- Despite the position, the channel occupancy in the pixel detector is typically an order-of-magnitude smaller than in the strip detector. Occupancy decreases stronger than area/ r^2 (magnetic field confines softer particles inside)
 - single pixel area = $100\mu m \times 150\mu m = 1.5 \times 10^{-2} mm^2$
 - typical strip area = $10 \text{cm} \times 100 \mu \text{m} = 10 \text{mm}^2$
- This plot explains why CMS tracking is heavily pixel driven (seeding).





Performances of CMS tracker system

- $\delta PT/PT \approx (1.5P_T + 0.5)\%$ with P_T in TeV, in the central region $|\eta| < 1.6$ and gradually degrading to $\delta P_T/P_T \approx (60P_T + 0.5)\%$ as $|\eta|$ approaches 2.5.
- Combining with muon chamber, P_T resolution is better than 10% for P_T upto 4 $\,\,$ TeV
- Efficiency >95% for hadronic track with PT >10 GeV and >98% for muon and >90% for electron











CMS electromagnetic calorimeter

• Design goal: Two photon mass resolution depends on the energy resolution and the angle between two photons.


 Measure 4-momentum of electron and photon with great accuracy


• Good two shower separation capability to reject a sufficient number of π carrying moderate energy (20-40 GeV)






• Average spread of the interaction vertices an additional 1.5 GeV contribution to diphoton mass resolution








$$p p \rightarrow H^0 \rightarrow Z Z$$


$$\downarrow \qquad \qquad \downarrow jet jet$$

$$\rightarrow e^+ e^-$$




PbWO₄ crystal calorimeter

- Over 80K lead tungstate crystal equipped with avalanche photon diodes and associated electronics operating at 4T magnetic field, a time of 25 ns bunch crossing and a radiation dose
 - 10^{13} neutrons/cm² and 1 kGy at $\eta = 0$ to 2×10^{14} neutrons/cm² and 50 kGy for $\eta = 2.6$.
- PbWO₄ calorimeter: short radiation length and Moliére radius, fast scintillation.
- Radiation does not have any affect scintillation and uniformity. But, affects the transparency of the crystals through the formation of colour centres due to crystal defects such as oxygen vacancies in the






Linearity of ECAL crystal: One can not get very long crystal, problem with manufacturing as well as nonlinearity due to self absorption, reflections on surfaces.



21


CMS electromagnetic calorimeter




Parameter	Barrel	Endcaps
Coverage	η <1.48	1.48< η <3.0
Δφ x Δη	0.0175 x 0.0175	0.0175 x 0.0175 to 0.05 x 0.05
Depth in X_0	25.8	24.7
# of crystals	61200	14648
Volume	8.14m ³	2.7m ³
Xtal mass (t)	67.4	22.0


Two lead blocks to start electromagnetic shower at endcap

1.9mm silicon strip pitch allows to determine impact position (~300 μ m at 50 GeV), \Rightarrow direction and as well as separation of single shower (γ) and overlaps of two close showers (π ⁰)




Preshower





- Opening angle of two photon in a decay of 100 GeV π^0 : ~2.7mrad, for 3m gap, separation of two photon ~8.1mm, whereas Moliere radius is 22mm (for PbWO₄)
- Preshower silicon strip detector will be used for π^0/γ rejection in the ECAL, CMS
- Strips of 1.80 mm width with a pitch of 1.9 mm (whereas crystal size 2.5cm×2.5cm and Moliere radius = 2.2cm)
- Area 63mm × 63mm




Preshower


- The preshower acts as a sampling calorimeter
 - Lead Absorber : initiate em showers
 - Silicon sensors : act as energy sampling
- Sampling calorimeter ⇒Poor energy resolution
- High momentum π^0 in forward direction \rightarrow smaller opening angle + Cost \rightarrow Preshower only in endcap region
- An energetic photon, accompanied by a nearby charged hadron/muon in a jet, may be misinterpreted as an electron.
- Can be distinguished in in first $1-2X_0$ of calorimeter (Preshower).
 - Three layer in upstream of ECAL
 - Single gamma: NO signal in first, several MIPs in next two
 - A $\pi^0 \rightarrow \gamma \gamma$: No signal in first, two multiple MIP clusters in next
 - An electron: MIP in 1st, and multi-MIP in next
 - A pion : MIP in all three layer
- Other than distinguishing electron/photon/pion/ π^0 ,
 - Angular measurements for photons
 - Clean-up of electron sample, by identifying $e + \gamma$ events


Radiation due to EM shower and reduction of albedo

- Radiation/neutron flux due to EM shower can damage silicon preshower/APD and can also produce large damage in tracking chamber
- Use polyethylene moderator to remove neutrino albedo from this EM shower




Vacuum fine-mesh phototriode (VPT)





Performances of CMS ECAL



Hadron calorimeter


• Requirement: Identification and measurement of quarks, gluons and neutrinos by measuring the energy and direction of jets and missing transverse energy flow of the events.

• Good missing energy a hermetic calorimetry coverage to $|\eta|$ <5 is required


CMS HCAL is constructed in 3 parts: Barrel ($|\eta| < 1.5$), Endcaps(1.5< $|\eta| < 3.0$) and forward (3.0< $|\eta| < 5.0$) (~10000 channels in total)

 Barrel HCAL (HB) + Endcap HCAL (HE) 17-18 Brass (laiton) plates (5.0cm thick) interleaved with plastic scintillator (4mm thick) embedded with wavelength-shifting optical fibres.

- Additional scintillation layers (HOB)
 are placed just outside the magnetic
 coil ⇒total depth ~11λ_{int}
- Scintillation light emission λ~410-425 nm
- Wave length shifter, peak at λ =490
- Megatiles are subdivided into size, $\Delta \eta \times \Delta \Phi = 0.087 \times 0.087$



Reading outs of tower tiles with WLS fibres



HCAL in construction phase






Forward hadron calorimeter (HF)


- Passive material: Steel instead of Cu, because of less activation under irradiation
- Active material: radiation resistant quartz fibre (d=300 μ m). Jet energy is measure by the Cherenkov light produced as charged particles passed through the quartz fibre, which is mainly electromagnetic component of showers, consequently good directional information. (~100 Mrad at η =5; 2%

loss in 30 Mrad)


- Signals to PMT, located in radiation shielded zones
- Segmentation $\Delta \eta \times \Delta \Phi = 0.175 \times 0.175$



CMS forward calorimeter: Same readout for EM/HAD



fast ~10 ns




20° wedges

Steel instead of Cu, because of less activation under irradiation (100Mrad in LHC)

Magnet system

• Field: 3.8 Tesla, Diameter: 14m (13m), length: 21.6m (5.9m), weight: 12000



For a similar bending power, the overall size of a solenoid system is smaller than that of a toroidal

4T → 3T ⇒Occupancy in the inner tracker increases by ~40%, outermost part of the barrel region by ~25%, in contrast it decreases by ~20% in the innermost areas.

4T field deduces particle flux in ECAL

CMS muon chambers

Muon chamber consists of four muon stations interleaved with the iron return yoke plates are placed behind the calorimeters.

The thickness of the absorber between the stations (30 to 75 cm) also prevents station-to-station correlations due to high energy muon radiation.

Position measurement:


Drift Tubes (DT) in barrel Cathode Strip Chambers (CSC) in endcaps


Trigger:

Resistive Plate Chambers (RPCs) in barrel and endcaps


195000 DT channels 210816 CSC channels 162282 RPC channels 4 Φ SL 4 η SL Honeycomb 4 Φ SL

Drift Tube






Characteristics of drift chamber



GAS: Ar/CO₂ (85/15) **HV**: Wires 3600 V Strips 1800 V I-beams -1800 V



long drift time tubes are cheaper than MWPC, but more sensitive to magnetic field, delta rays and e.m.showers

use of cool gas (Ar/CO_2) , accurate field shaping (4 electrodes), many staggered layers redundancy generates robustness against neutron and e.m. background and allow prompt measurement of time, position and angle of passage of a track for MU trigger

Cathode strip chambers

- Magnetic field is very intense (up to several tesla) and very inhomogeneous.
- Two co-ordinates are available by the simultaneous and independent detection of the signal induced by the same track on the wires and on the strips (six plane chamber).
- Strip width = 3 16 mm, anode wire gap = 3.12 mm, chamber gap 9.5mm, 50 μ m Au-tungsten with tension 350g, Gas mixing : Ar-CO₂-CF₄ (30 % 50 % 20%)


468 CSCs

140K Anode channels

170K Cathode channels

360 10° CSCs

- •3/2: 144 Large CSCs (3.4x1.5 m²):
- •1/2/3 : 216 Small CSCs $(1.8x1.1 \text{ m}^2)$:
- •108 (1/2/3) : 20° CSCs $(1.9x1.5 \text{ m}^2)$:
- •Frontend Electronics:
 - ~2,000,000 wires
 - ~6,000 m² sensitive area



wires

35

precision(trigger) δ $r_{_{0}}$ ~1 mm , δr ~1 cm, δt ~4ns, (offline) $\delta r_{_{0}}$ ~100 μm

Resistive plate chamber

- High gas gain without developing streamer/spark
- The strips are oriented parallel to the tubes in the barrel (one RPC layer in station 3 and 4 and two in 1 and 2) and to the radial strips in endcap CSCs. The pattern of hit strips gives a measure of muon momentum ⇒ trigger.


• With proper choice of the resistivity and plate thickness, the rate capability can reach

several thousand Hz/cm².

•
$$C_2H_2F_4$$
 - i- C_4H_{10} (95.5% - 4.5%)


- Efficiency ~100% at 8.5 kV
- Timing resolution = 1.7 ns
- $6\eta \times (36 120) \Phi \text{ (endcap)}$
- 5/16 degrees in Φ (barrel)

Rejection of backgrounds, which arise from hadronic punch through, debris from muon interactions with matter, thermal neutrons, beam halo in the forward direction, noise in the electronics etc




Detecting strips


lonizing



CMS, a large complicated detector




CMS design to reality



Chronological steps towards Large Hadron Collider

- 1983 : Z⁰/W[±] discovered at SPPS proton-antiproton collider. S. Myers and W. Schnell proposed twin-ring *pp* collider in LEP tunnel
- 1984: Workshop in Lausanne on installing a Large Hadron Collider (LHC) in the LEP tunnel
- 1987: CERN's long-range planning committee chaired by Carlo Rubbia recommended LHC as the right choice for lab's future
- 1989: ECFA Study Week on instrumentation technology for a high-luminosity hadron collider; Barcelona; LEP starts operation, injection 14th July, collision 13th Aug
- 1990: ECFA LHC workshop, Aachen
- 1992: General meeting on LHC physics and detectors, Evian-les-Bains
- 1993: Letters of intent for LHC detectors submitted: SSC termination
- 1994: Technical proposals for ATLAS and CMS approved
- 1998 : Construction begins
- 2000: CMS assembly begins above ground; LEP collider closes
- 2003: ATLAS underground cavern completed and assembly started
- 2004: CMS cavern completed
- 2007: Experiments ready for beam
- 2008: First proton beam in LHC tunnel
- **2009 : First proton-proton collisions**
- 2010: First physics results
- 2011-: Exploring Higgs- BSM....
- **2012 : Discovery of Higgs**

LHC/HL-LHC Plan




Jan 127


Date


Jan 12


Pileup and radiation dose











CMS Upgrade Program

LS1 consolidation: Complete detector & consolidate operation for nominal LHC beam conditions ~13 TeV, 1 x Hz/cm², <PU> ~25

- Complete Muon system (4th endcap station), improve RO of CSC ME1/1 & DTs
- Replace HCAL HF and HO photo-detectors and HF backend electronics
- Tracker operation at -20°C
- Prepare and install slices of Phase 1 upgrades

Phase 1 upgrades: Prepare detector for 1.6 x 10^{34} Hz/cm², <PU> ~40, and up to 200 fb⁻¹ by LS2, and 2.5 x 10^{34} Hz/cm², <PU> ~60, up to 500 fb⁻¹ by LS3

- New L1-trigger systems (Calorimeter Muons Global)
- New Pixel detector (ready for installation in 2016/17 Year End Technical Stop)
- HCAL upgrade: photodetectors and electronics (HF 2015/16 YETS, HB/HE LS2)

Phase 2 upgrades: $\gtrsim 5 \times 10^{34} \, \text{Hz/cm}^2$ luminosity leveled, <PU> ~128 (simulate 140), reach total of 3000 fb⁻¹ in ~10 yrs operation

- Replace detector systems whose performance is significantly degrading due to radiation damage
- Maintain physics performance at this very high PU

LS2 2018

LS1


2013-14

LS3 2022-23

CMS upgrade program

LS1 Projects

- Complete Muon coverage (ME,RE4)
- Improve muon operation, DT electronics
- Replace HCAL photo-detectors in Forward (new PMTs) and Outer (HPD→SiPMs)
- DAQ1→DAQ2



Phase 1 Upgrades

- New Pixel detector, HCAL electronics and L1-Trigger upgrade
- GEMs for forward muon det. under review
- Preparatory work during LS1
 - New beam pipe for pixel upgrade
 - Install test slices of pixel, HCAL, L1-trigger
 - Install ECAL optical splitters for L1trigger

Phase 2: being defined now

Tracker replacement, L1 Track-Trigger

LS₃

- Forward: calorimetry, muons and tracking
- High precision timing for PU mitigation
- Further Trigger upgrade
- Further DAQ upgrade


Medium term (LS1 to LS2): pixel


Install in YET 2016-17

Features of New Design


- Robust design: 4 barrel layers and 3 endcap disks at each end (124M channel from 66M)

- Four hit coverage in whole tracking range, $|\eta|$ <2.5
- Smaller inner radius (44mm -> 29mm) (new beampipe), large outer
- New readout chip with expanded buffers, embedded digitization and high speed data link
- Reduced mass with 2-phase CO₂ cooling, electronics moved to high eta, DC-DC converters






Upgrade of CMS Forward HCAL



- Appear in one channel
- **■In time with collisions**
- **Caused by C^v light by particles going through PMT glass**


LS1: Single anode PMT to multi-anode PMT

- Thins glass window (effect of Cherenkov light is 25%)
- Metal envelope (remove Cherenkov from side)
- Increase in Quantum efficiency



New Back-Ends (microTCA etc)

Near future upgrade plan of CMS central HCAL



Paramount to maintain efficient Particle flow approach in high pileup environment

v. 2017-06-A

16

HE

HΕν


YET


- HPD unforeseen features (B-field, gain drifts)
- Improved S/N and depth segmentation added for full barrel (e±/γ identification) / endcap (radiation damage to scintillator)
- Improved calibration, bkg & PU suppression, EM isolation (analysis and trigger)
- New electronics with broader dynamic range, TDC capability (identifying anomalous signal in HF and isolation in HB/HE)


Install front-end and back-end electronics

Phase 2: Tracker in Level-1 Trigger


- Higher radiation resistance, higher readout granularity
- Without tracker input muon triggering becomes saturated
- A trigger-capable tracker could take advantage of strong CMS magnetic field
 - Send only selected hits for Level-1 Trigger (Pt threshold of 1GeV or more)
 - (L1 tracks using stubs and) refine trigger primitives from calorimeters and muon, electron trigger rate reduce by a factor of 10)
 - Binary readout for the strip tracker









CMS Tracker Upgrade for the HL-LHC



Timing information to remove Pileup track






3

Timing layers at CMS


- Thin layer between tracker and calorimeters
- ~30 ps resolution for charged tracks (above 0.7 GeV)
- Hermetic coverage for $|\eta| < 3.0$

Integration with tracker in


2024



CMS ECAL history of laser transparency measurement subdivided by eta regions



Response of HE scintillator and upgrade plan



0.8

0.75

thin lines L1/ieta28, HPDs

thick lines L1/ieta28, SiPMs

16

Int. Lumi [fb⁻¹]

20

- Continue to use same scintillator till larger radius
- LS3 and then also use scintillator at 55


CMS HGCAL upgrade plan

- Silicon/Scintillator detector in the high/low radiation region
- 28layers in the ECAL (CE-E) + 24 layers in HCAL (CE-H)
- Trigger and reading data of >6M channels at 40MHz

•	Endcap	coverage:	1	.5 <	η	< 3.0
---	---------------	-----------	---	------	---	-------

• Total power at end of HL-LHC ~180 kW@-30 $^{\rm o}$ C

Total	Silicon sensors	Scintil lators
Area (m ²)	600	500
# of modules	27000	4000
Cell size (cm ²)	0.5 - 1	4 – 30
# of channels	6M	0.4M



High-Granularity Calorimeter (HGCAL)

Initial design:

Number is varying: So this is not final number

ECAL: ~33 cm, 25 X_0 , 1 λ , 31 layers:

- $_{0}10$ planes of Si separated by $0.5 X_{0}$ of lead/Cu
- $_{0}10$ planes of Si separated by $0.8~X_{0}$ of lead/Cu
- $_{0}10$ planes of Si separated by 1.2 X_{0} of lead/Cu

.HCAL: ~66 cm, 3.5λ:

- □12 planes of Si separated by ~0.3l of absorber □Fine grain pads 0.5~1cm²
- ~10M channels and 700m2 of Silicon


Back HCAL as HE re-build 5λ


With increased granularity

 $\Delta E/E \sim 20\%/\sqrt{E}$; 3D shower reconstruction


=> Use detailed shower topology to mitigate PU effect

Area of Silicon(m2)	ECAL	HCAL	Total
Channels	10.0M	3M	13M
Detector module	18.2k	10.5k	28.7k
Weight(one endcap (tones)	18	81	99







Module type distribution EE-HGC (initial design)



Sensor Surface cm² Square Hexagonal


6" wafers ~ 100 ~ 130 8" wafers ~ 180 ~ 230 300um / 256 ch 200um / 256 ch 100um / 512 ch







Possible Sensor Parameters

Si Thick	300	200	100	um
Max Fluence	6.4×10 ¹⁴	2.5×10 ¹⁵	1×10 ¹⁶	n/cm ²
HGC EE Area	220	120	140	m2
Vbias	600~900	600~900	600~900	V
Signal	15,000	7,500	6,000	e-
Ileak Power/Module	0.5~0.7	1.4~2.1	2.7~4.1	W/module
Ileak Power	5~7	7~11	16~25	kW



Simulations






CERN beam to	est in
2016-2018 for	the
validation	

$\rho \text{ (mm)}$	$\left(\frac{\sigma_{\mathrm{E}}}{\mathrm{E}}\right)_{\mathrm{stoch}}$	$\left(\frac{\sigma_{\mathrm{E}}}{\mathrm{E}}\right)_{\mathrm{cte}}$
∞	0.209 ± 0.001	0.0056 ± 0.0001
2.5	0.280 ± 0.001	0.0130 ± 0.0001
7	0.237 ± 0.001	0.0090 ± 0.0001
25	0.216 ± 0.001	0.0069 ± 0.0001
dynamical	0.228 ± 0.001	0.0128 ± 0.0001

Imaging Showers with the HGCAL





Forward muon detector upgrade : GEM




B-physics at e⁺e⁻ machine : CLEO-II-III

Started with ARGUS and continued long time with CLEO









Ring Imaging Cherenkov (RICH) counter was necessary to identify K/π mainly for the CP-violation study $_{63}$


Principle of time dependent CPV measurement




- 1. Fully reconstruct one B-meson which decays to CP eigenstate
- 2. Tag-side determines its flavor (effective efficiency, $\varepsilon D^2 = 30\%$)
- 3. Proper time (Δt) is measured from decay-vertex difference (Δz)
- 1. Low momentum π
- 2. High momentum π/K
- 3. Charge of lepton
- 4. Same side tag (B^{*+})

KEK-B Collider





Belle Detector




Chronological steps towards BELLE

- 1973: Third generation to accommodate CP violation
- 1977: Discovery of bbar-b bound state
- 1980 : Possibility of larger CP violation in neutral B decays Carter and Sanda
- 1981 : Evidence of $\Upsilon(4S) \rightarrow B$ bar-B (CLEO)
- 1983 : Observation of long B life time (MAC, MARK-II)
- 1987: Large mixing in the neutral B meson system (ARGUS, UA1)
- 1991 : Concept of asymmetric B factory
- 1994: Letter of Intent
- 1995: BELLE Technical Design Report
- 1999 : First asymmetric e⁺e⁻ interactions in KEKB
- 2003 : >100M Bbar-B events
- 2008: Nobel Prize for Makoto Kobayashi and Toshihide Maskawa
- $2011 :> 1 \text{ ab}^{-1} \text{ of data}$

Belle silicon detector: DSSD

SVD sideview



xy Impact Parameter Resolution Resolution (µm) 2250 200 200 $19 \oplus 50/p\beta*\sin(\theta)^{3/2} (\mu m)$ - cosmic ray - e e → μ μ 175 150 125 100 75 25 $5 \quad 6 \quad 7 \quad 8$


A p-stop structure is used to isolate strips on ohmic side (n-side)

$$\sigma_{IP_{R\varphi}} = \frac{\alpha_{MS}}{P\sin^{3/2}\theta} \oplus \sigma_{0,R\varphi}$$


102 DSSD : size =
$$57.5 \times 33.5 \text{ mm}^2$$
 : total channel = 81920 ; S/B ~ 19

102 DSSD: size = 57.5×33.5 mm²:
$$\sigma_{IP_{Rz}} = \frac{\alpha_{MS}}{P \sin^{5/2} \theta} \oplus \sigma_{0,Rz}$$

	size	pitch	width
Z -strip(n)	53.5×32.0 mm ²	42μm	14 μm
Ф-strip (р)	54.5×32.0 mm ²	25μm	12 μm



Central Drift Chamber (CDC) @ Belle




- 10⁶
 (a) Gas Gain
 (b) Drift Velocity

 10⁵
 (a) Gas Gain
 (b) Drift Velocity

 10⁸
 (c) A
 (d) Gas Gain
 (e) A
 (e) B
 (f) C
 (f) A
 (f) C
 (f) C
- 50 layer of anode wire, 8400 drift cell
- Concave shape to balance wire tension
- Less multiple Coulomb scattering but reasonable dE/dx for PID He- C_2H_6
- Nearly constant drift velocity

Details in wire configurations




Configurations of the CDC sense wires and cathode strips


Superlayer type and no.	No. of layers	Signal channels per layer	Radius (mm)	Stereo angle (mrad) and strip pitch (mm)
Cathode	1	$64(z) \times 8(\phi)$	83.0	(8.2)
Axial 1	2	64	88.0-98.0	0.
Cathode	1	$80(z) \times 8(\phi)$	103.0	(8.2)
Cathode	1	$80(z) \times 8(\phi)$	103.5	(8.2)
Axial 1	4	64	108.5–159.5	0.
Stereo 2	3	80	178.5–209.5	71.46–73.75
Axial 3	6	96	224.5-304.0	0.
Stereo 4	3	128	322.5–353.5	-42.2845.80
Axial 5	5	144	368.5–431.5	0.
Stereo 6	4	160	450.5-497.5	45.11-49.36
Axial 7	5	192	512.5-575.5	0.
Stereo 8	4	208	594.5-641.5	-52.6857.01
Axial 9	5	240	656.5–719.5	0.
Stereo 10	4	256	738.5–785.5	62.10-67.09
Axial 11	5	288	800.5-863.0	0.

Track reconstruction π (K_s) $\pi^+(K_s)$ e⁺(J/ψ) K (tag) **BELLE** e (J/ψ) 0.4 5 [12 (Ptdown. Pt up) ((Ptdown+Pt up)] (%) Spatial resolution (mm) 0.35 0.25 0.2 1.6 Fit (0.20±0.003)% Pt⊕ (0.290±0.006)% 1.2 0.8 0.15 0.1 0.05 2 3 Pt (Gev/c) Signed distance from sense wire (mm)

BELLE TOF detector



Backward




Forward


• High B-field Operation

 HamamatsuR6680 Fine Mest **PMTs**


- 24 stages
- 2000 mesh/in.
- $G>3\times10^6$ in 1.5T field
- **TSC** radius = 118 cm
- **TOF** radius = 120 cm




Particle identification at BELLE (K,π,p)



Particle identification (K)




BELLE electromagnetic calorimeter




Total # of crystal = 1152 + 6624 + 960 of dimensions $5.5cm \times 5.5cm$ $(6.5cm \times 6.5cm) \times 30cm$ in barrel and in endcaps, front face =4.45cm to 7.08cm and backend = 5.4cm to 8.2cm with length of $30cm(16.2X_0)$


3 x 3 matrix with 0.5 MeV threshold


Performance of ECL







Calibration: $\pi/\eta \rightarrow \gamma\gamma$, $D^* \rightarrow D\gamma$ E (Calorimeter) /P(tracker)









ECL calibration with data






 Data was corrected using these two calibrations

• Belle note # 583 & 718







for $D^a \to k^-$ for photoi energy greater than 300 MeV data: EXP07-EXP19.

78




- Two parallel electrodes with high bulk resistivity
 - $-\sim 2\times 10^{12} \Omega$ -cm : glass,
 - $\sim 10^{10} \ \Omega$ -cm : bakelite)
 - $\sim 10^4 \ \Omega$ -cm : undepleted silicon
 - $1.68 \times 10^{-6} \Omega$ -cm : Cu
 - $-7.5 \times 10^{19} \Omega$ -cm : Quartz
- A local discharge of the plates due to initiation of streamer by an ionising particle
- Gain ~10⁶ (avalanche mode) and 10⁸ (streamer mode)
- Discharge limited by high resistivity and quenching characteristics of the gas
- Induced signal on external pickup strips
- Position and timing information
 - Strip size $19mm(47mm) \times 2m (5m)$
 - Applied H.V. 8kV/1.9 mm
 - Timing resolution : few ns
 - Rate < 0.2 Hz/cm²






Performance of KLM






$B^0 \rightarrow J/\psi K_S^0$







Asym. = $-\xi_{CP}\sin 2\phi_1\sin \Delta m \Delta t$

$$\sin 2\phi_1 = +0.643 \pm 0.038$$


A = -0.001 \pm 0.028

$$\sin 2\phi_1 = +0.641 \pm 0.057$$

A = +0.045 ±0.033


All results of $b\rightarrow ccs$ and $b\rightarrow ccd$ are consistent with each other


Observation of $(J/\psi\pi^+\pi^-)$ peak in B $\to J/\psi\pi^+\pi^-$ K signal



Inclusive B→XK from BaBar

- Fully reconstruct one B
- Measure p(K) in the other B frame
- Calculate m(X) based on p(K)





BF($B^{\pm} \rightarrow K^{\pm} c\overline{c}$) are consistent with PDG values for known charmonia

Efficiency ~0.5%


Determined lower/upper limits on absolute BF's

 $B(B^{\pm} \rightarrow K^{\pm}X(3872)) < 3.2 \times 10^{-4} @ 90\% CL$

 $B(X(3872) \rightarrow \pi^{+}\pi^{-}J/\psi) > 4.2\%$ @ 90% CL

Observation $D^0D^0\pi^0$ threshold peak in $B \to D^0\overline{D}{}^0\pi^0K$ signal

 D^0 reconstruction : $K^-\pi^+,\,K^-\,\pi^+\pi^\square\pi^+,\,K_S^-\pi^+\pi^-$ and K^+K^-




Fitted peak, M=3875.4 \pm 0.7^{0.7} \pm 0.8 MeV

$$\frac{\text{Br}(X \to D^0 \overline{D^0} \pi^0)}{\text{Br}(X \to \pi^+ \pi^- J/\psi)} = 9 \pm 4$$



Threshold enhancement in $B \rightarrow (D^0 \overline{D}^{*0}) K$



The mass is also 2.5σ above the nominal X(3872) mass




Signals in $J/\psi \pi \pi$ and $D^0 \bar{D}^0 \pi^0$ are due to same or different particle?

Motivation for BELLE2 experiment


- Measurements of rare decay modes (e.g., $B \rightarrow \tau v, D\tau v$);
- Observation of new charmonium-like and bottomonium-like hadronic states;
- $b \rightarrow s$ transitions: probe for new sources of CPV and constraints from the $b \rightarrow s\gamma$ branching fraction;
- Forward-backward asymmetry (AFB) in $b \rightarrow sl^+l^-$ has become a powerful tool to search for physics beyond SM;
- Observation of DD mixing;
- Search for lepton flavour violation in τ decays;
- Study of the hadronic τ decays;
- Precise measurement of the hadronic cross sections in $\gamma\gamma$ and e^+e^- (γ ISR) processes

Belle-II



KEKB: Beam Energy 3.5/8.0 to 4.0/7.0 GeV, L (10^{34}) : 2.11 to 80

Belle/II upgrade – side view




Two new particle ID devices, both RICHes:

Barrel: Timé-Of-Propagation (TØP) or focusing DIRC

Endcap: proximity focusing RÍCH

Belle-II: TOP counter


Cherenkov ring imaging is used as timing information



Difference of path length

→ Difference of time of propagation (TOP) (+ TOF from IP)

With precise time resolution (σ ~40ps)



√2400mm

20mm


Particle-id with Aerogel RICH


Multi layer Aerogel from

NIM A548 (2005) 383

stack two tiles with different refractive indices: "focusing" configuration


developed and proposed for Super-Belle endcap region to improve π/K







Test beam results:

5.5 σ π/K separation at 4 GeV with 9 pe and promise of ToF






Upgraded vertex detector



 SVD: 4 layer Si strip detector (DSSD) (R = 3.8, 8.0, 11.5, 14.0 cm)

PXD: 2 layer Si pixel detector (DEPFET technology) (R = 1.4, 2.2 cm) monolithic sensor thickness 75 μm (!), pixel size 50 x 55 μm² to 50 x 85μm² (depending on layer and z)


Significant improvement in z-vertex resolution



LHCb detector

Horizontal: ± 300mrad

Vertical : ± 250mrad




Characteristics of hadronic b production in hadron collider


80

20


- $B_s \& \Lambda_b$ and other b-flavored hadrons are accessible at hadron collider.
- The higher momentum b's are at larger η's
- b production peaks at large angles with large bb correlation



LHCB VELO detector



LHC-B RICH system



100


Momentum (GeV/c)

0


Two RICH detectors covering the particle momentum range 1 to 100 GeV/c using aerogel, C_4F_{10} and CF_4 gas


RICH signals in LHCB

• $B \rightarrow \pi^+ \pi^-$ signal at LHCB simulation



Performances of LHBb RICH





Radiator	$N_{\rm pe}$ from data		$N_{\rm pe}$ from simulation
	$D^0 o K^- \pi^+$	$pp \to pp\mu^+\mu^-$	$D^0 o K^-\pi^+$
Aerogel	5.0 ± 3.0	4.3 ± 0.9	8.0 ± 0.6
C_4F_{10}	20.4 ± 0.1	24.5 ± 0.3	28.3 ± 0.6
CF_4	15.8 ± 0.1	17.6 ± 0.2	22.7 ± 0.6

Surface quality in aerogel

QE of photo-cathode


Resolutions in LHC-b RICH detector

Single Photon Cherenkov Angle Resolutions in mrad.


- Chromatic: From the variation in refractive index.
- Emission Point: Essentially from the tilt of the mirrors.
- Pixel Size: From the granularity of the Silicon detector pixels in HPD
- PSF (Point Spread Function):From the spread of the Photoelectron direction as it travels inside the HPD,(from the cross focusing in the electron optics)

Component and overall (mrad)	Aer ogel	C ₄ F ₁₀	CF ₄
Chromatic	2.36	0.90	0.46
Emission point	0.38	0.82	0.36
Pixel size	0.52	0.52	0.17
PSF	0.54	0.53	0.17
Overall RICH	2.53	1.44	0.66
Overall RICH + Tracks	2.60	1.60	0.70
Average number of photon	5.3	24.0	18.4


Performances of LHCb RICH




History: A detector for toponium!



- The best ECAL at that time
- But, to reduce cost, size of tracker became very small; TEC (80% $CO_2+20\%$ iC_4H_{10}), +1atm to reduce drift velocity by an order (6µm/ns)



Misc. point on L3 experiment



- i-butane in calorimeter was not allowed due to safety reason
- Though no material inbetween muon chamber, multiple scattering of muon in calorimeter deteriorate the performance of momentum measurement, ALEPH has better performance as well as B-tagging

LHC Heavy Ion Program

Machine

Energy:

```
\odot E<sub>beam</sub> = 7 x Z/A [TeV] => \sqrt{s} = 5.5 TeV/A or 1.14 PeV (Pb-Pb)
```

Beams:

• possible combinations: pp, pA, AA (constant beam rigidity)

heavy ion running:

• ~ 4 weeks/year(10⁶ s effective); typically after pp running (like at SPS)

luminosity:

- integrated luminosity 0.5 nb⁻¹/year (Pb-Pb)

Detector(s)


one single dedicated 'general purpose' HI expt at LHC: ALICE

- **○** RHIC: 2 large multipurpose + 2 small special purpose expts

Comparison with previous experiments


Qualitatively new regime

- Probe initial partonic state in a novel Bjorken-x range (10⁻³ 10⁻⁵):
 - nuclear shadowing,
 - high-density saturated gluon distribution (CGC)
 - effectively moves
 RHIC forward region
 to mid-rapidity at
 LHC
- Larger saturation scale $(Q_S=0.2A^{1/6}\sqrt{s^\delta}=2.7~GeV)$ particle production dominated by the saturation region



Comparison with previous experiments

Qualitatively new regime




Observables in ALICE detector

- Particle multiplicities (number)
- Particle spectrum (momentum)
- Particle Correlations
- Jets
- Direct photons
- Di-leptons
- Heavy quark and quarkonia
- Cosmic ray muon

Need large detector interms of size, granularity, complexity

ALICE Tracking Challenge





STAR: 500 particles in fiducial volume


ALICE: $dN/d\eta = 8000$



A Large Ion Collider Experiment (ALICE)








Physics goals for ALICE upgrade

Charm/beauty meson and baryon production in a wide momentum range, down to very low p_{T}

- Probe the quark-medium interaction (in-medium energy loss) and the QGP transport coefficients
- Study degree of charm thermalization and possible hadronization via coalescence
- J/ ψ , ψ ' states and prompt/non-prompt J/ ψ separation down to lowest $p_{\rm T}$ in wide rapidity range
 - Charmonium dissociation and regeneration pattern as a probe of color deconfinement and medium temperature
- Measurement of low-mass and low- $p_{\rm T}$ di-leptons (vector mesons, thermal virtual photon)
 - Initial temperature, space-time evolution and equation of state of the QGP
 - Chiral-symmetry restoration → modification of r spectral function
- Jet quenching and fragmentation: PID of jet particle content, heavy flavour tagging
- Light nuclei and hyper-nuclei
 - Study their production mechanisms and degree of collectivity
- For most of these observables S/B is very low, so it is not possible to implement dedicated triggers.

ALICE detector upgrade




Tracking in ALICE


Robust, redundant tracking from 100 MeV to 100 GeV

- modest solenoidal field (0.5 T) => easy pattern recognition
- long lever arm => good momentum resolution (BL² : Alice ~ CMS
 > Atlas !)
- small material budget: $< 10\% X_0$ vertex \rightarrow end of TPC
- Beryllium beam pipe of outer radius 2.98cm and thickness 0.8mm 3.5m (RB24 and copper) and 0.4m (RB26 and stainless steel)
- -Inner Tracking System (ITS): Design considerations:
 - -Primary vertex resolution <100 μm
 - -Reconstruct secondary vertices of B,D mesons
 - –Stand along tracking at low $p_{\rm T}\,$ and provide dE/dx measurements for low momentum track
- **–Constraints :** Space (4 cm < r < 44 cm), integrated radiation doses 2.2kGy and 10^{12} n cm⁻² and particle flux $80/cm^2$ in innermost layer and $1/cm^2$ in outermost layer

Silicon vertex detector (ITS)


- -Three different types of silicon detectors (at r=3.9,7.6,14.0,23.9,37.8/38.4, 42.8/43.4cm)
 - -Two silicon pixel layers $(\sigma_{r-\phi}=12\mu m \text{ and } \sigma_z=100\mu m)$
 - –Two silicon drift layers ($\sigma_{r-\phi}$ =38 μm and σ_z =28 μm)
 - -Two double sided silicon strip layers with angle stereo angle 7.5 mrad and 27.5 mrad ($\sigma_{r-\phi}$ =20 μ m and σ_z =830 μ m)
 - -Total readout channels >12M (mainly pixel readout)






ITS upgrade objectives

- Improve track DCA resolution, in particular at low P_T (~3(5) in r ϕ (z) @PT=500 MeV/c)
- Improve tracking efficiency and P_T resolution at low P_T
- Increase read-out rate : 1 kHz \rightarrow 50 kHz in Pb-Pb, 200 kHz in pp
- Withstand radiation load (10 years operation):
 - TID ~270 krad, NIEL : ~ 1.7×10^{12} 1MeV neq/cm²
- Easier maintenance
- Implementation :
 - 7-layer barrel geometry of Monolithic Active Pixel Sensors (MAPS)
 - First layer closer to IP ($r0 = 39mm \rightarrow 22mm$)
 - Smaller beam pipe : $29mm \rightarrow 18.2mm$
 - Reduced material budget, in particular for the 3 innermost layers
 - X/X0 = 1.14% →0.3% for the first layers
 - Silicon thickness: 50 μm
 - − Smaller pixel size : $50\times425\mu\text{m}^2 \rightarrow 25\times25\mu\text{m}^2$
 - Increase number of layers $6 \rightarrow 7$




Time Projection Chamber (TPC)

- $|\eta|$ <0.9 (~1.5 with reduced track length poorer resolution)
- 88 m³ of Ne/CO₂ (90%/10%), minimum diffusion for better positioning
- Material is less than 3.5% for normal incident
- Rate capability is restricted due maximum drift time 90µs at 100kV (field 400 V/cm)




- MWPC with cathode pad readout : In total 560K pads with size (4×7.5 mm² for inner segment, 84.1cm<2<132.1cm and 6×10mm² & 6×15mm² for outer segment, 134.2cm<r<246.4cm)
- Expected pad occupancy 40-15% (inner/outer radius)
- dE/dx resolution : 5.5/6.9% for isolated (dN/dy=8000) track
- Momentum resolution : 1-2% for track 100 MeV to 1 GeV and 10% for p_T =100 GeV


Vertex and Impact parameter



Momentum resolution of track and invariant mass



Existing TPC: Rate Limitation





Gating grid

- Open during drift time to allow electron into MWPC
- Closed afterwards to prevent ion back-flow
- Limits readout rate 3.5kHz
- Opening GG permanently not possible
 - Ion back flow creates large space charge
 - Space point distortion up to 1m not tolerable

TPC upgrade objectives

- Main objective: Retain physics performance in high rate operation
 - continuous read-out of Pb-Pb events at 50 kHz collision rate
- Operation of MWPC without gating grid would lead to massive space-charge distortions due to back-drifting ions
- Instead: Continuous read-out with micropattern gaseous detectors
- Advantages:
 - reduced ion backflow (IBF)
 - high rate capability
 - no long ion tail
- Requirements for read-out system:
 - IBF < 1% at gain 2000
 - dE/dx resolution < 12% for ⁵⁵Fe
 - Stable operation under LHC conditions







GEM setup with S and LP foils


α (%)

dE/dx

- IBF and energy resolution studies for baseline solution (4GEM stack)
- Different foil configuration, V_{GEM} , E_{T} (transfer fields)








- IBF optimised settings : High $E_{T1} \& E_{T2}$, low E_{T3} , $V_{GEM1} \approx V_{GEM2} \approx V_{GEM3} << V_{GEM4}$
- Achieved performance : 0.6 0.8 % IBF at (5.9 keV) ~ 12%


Transition radiation detector (TRD)

• Electron identification in the central barrel for momenta great than 1 GeV


• Five layers of 4.8cm thick radiate TRD chamber (Fibres/foam sandwich) and MWPC readout chamber (Xe :Cl = 85%:15%) with 2.9m<r<3.7m


- Pad occupancy ~34%
- Position resolution ~600μm and 2cm in (r-φ and z measurement)
- Total readout channel 1.16M
- Momentum resolution $\delta p/p = 2.5\% \oplus 0.8 \times p\%$
- Radial detector thickness 15X₀
- Due to properties of fast tracker, it can be used as an efficient trigger for high transverse momentum electron






Electron identification









Time-Of-Flight (TOF)

- Particle identification (PID) in the intermediate momentum range (from 0.2 GeV to 2.5 GeV)
- Constraints : Not exceeding occupancy 10-15%
- A group of Multi-gap Resistive Plate Chamber (15 in the central, 19 in the intermediate and I the external modules), radial distance from 3.7m to 3.99m
- Radial thickness 0.18X₀
- Gas composition : $C_2H_2F_4(90\%)$, i- $C_4F_{10}(5\%)$, $SF_6(5\%)$
- Typical size: 122cm long and 13cm width, subdivided in pad size 35mm × 25mm²
- Readout channel: 157K
- Expected timing resolution ~40ps




High Momentum Particle Identification Detector (HMPID)

- Extend PID up to 3 and 5 GeV π/K and K/p discrimination
- Seven Proximity Focusing Ring Imaging CHerenkov (RICH) counters of size ~1.5m×1.5m)
- Coverage : $-0.6 < \eta < 0.6$ & Azimuthal coverage 57.61 $^{\circ}$
- n=1.2989 at λ =175nm $\Rightarrow \beta_{min} = 0.77$ (p_{th} = 1.21m)
- Photo-electron conversion through 6 independent CsI photocathode (QE=25%) board, 64×40cm², segmented into pads 8×8.4mm²
- Amplification: 20μmΦ W-Re anode wires separated from cathode and collection wire plane (100 μm gold plated Cu/Be) by 2mm
- Material budget 0.18 X₀




ALICE HMPID




PHOton Spectrometer (PHOS)

- Detected electromagnetic particles in a limited acceptance domain at central rapidity and identification of photon as well as π^0 , η through two photon decay
- Requirements: Identification, high resolution, (energy & spatial) with large dynamical range (100 GeV with least count 5-10 MeV)
- Coverage: $-0.12 < \eta < 0.12 \& \Delta \Phi = 100^{\circ}$
- Photon detector : An array of 56 rows and 64 columns PbWO₄ crystal of size $22 \times 22 \times 180$ mm³ (Moliere radius = 22mm and X_0 = 8.9mm) operated at -25° C with precision 0.3° C (dN/dT=-2%)
 - 5×5 cm² Avalanche Photodiode (APD) readout
- Charge particle veto detector : 14mm active volume of proportional chamber filled with $80\% Ar/20\% CO_2$. 256 anode wires, $30\mu m$ in Φ stretched 7mm above cathode of pitch 5.65mm. Cathode planes are segmented into 7168 of $22 \times 10.5 \text{ mm}^2$.
- Its charge particle identification is better than 99% with material budget $0.05X_0$ and sensitive area ~1.8m².
- $6 \times 6 \times 24.6$ cm³ for EMCAL : 77 layer of 1.44mmPb/1.76mm scintillator, $X_0 = 12.3$ mm, $R_M = 3.2$ cm, # of r.l. = 20,

LS1: EMCal Extension/Upgrade



Reconstruction of γ and π^0





Particle Identification



Alice uses ~ all

known techniques!


- I stable hadrons (π , K, p): 100 MeV < p < 50 GeV
 - dE/dx in silicon (ITS) and gas (TPC) + Time-of-Flight (TOF) + Cerenkov (RICH)
 - ☐ dE/dx relativistic rise => extend PID to several 10 GeV
- Π decay topology (K⁰, K⁺, K⁻, Λ , D⁺,...)
 - ☐ K and Λ decays up to > 10 GeV
- leptons (e, μ), photons, η, π^0



electrons in TRD: p > 1 GeV

muons: p > 5 GeV


 π^{0} in PHOS: 1 < p < 80 GeV





PID at High Momentum






■ TPC dE/dx


- 5.5% (pp) -> 6.5% (central Pb)
- Π π /K/p spectra up to ~ 50 GeV
 - [limited by statistics
 - requires goodsystematics (calibrate with data)

 $\pi/K/p = 2:1:2$




dE/dx

PID at ALICE




Forward Detectors






New Fast Interaction Trigger detector

- To replace V0 and T0 detectors
- Requirements:
- -Preserve resolution
- -Increase acceptance
- -Integrate detectors
- Good Time resolution < 30 ps Time zero for PID
- Large acceptance
- Trigger efficiency, centrality, beam gas background reduction, for pp and Pb-Pb, veto forward hadronic activity for the detection of ultra-peripheral Pb-Pb collision
- •Finer segmentation
- Reaction plane determination




T0C+: $-3.3 \le \eta \le -2.2$




T0A+: $3.8 \le \eta \le 5.4$

V0+: $2.2 < \eta < 5.1$

FIT = T0 + and V0 +





T0+ modules

- Improved T0
- Rectangular quartz radiators
- New sensors MCP-PMT
- Larger acceptance
- More channels
- Upgraded electronics and readout


V0+ sectors

- Improved V0
- Faster plastic scintillator
- Monolithic structure
- Reduced fibre length
- New sensor (SiPM or MCP-PMT)
- New electronics and readout



Dimuon Spectrometer





Study the production of the J/9, 9, 5, 5, 5, 5, decaying in 2 muons, $2.4 < \eta < 4$

Resolution 70 MeV at the J/ Ψ , 100 MeV at the Y

4 RPC Trigger Chambers

Filter

10 planes of high granularity pad tracking chambers, over 800k channels

B Tracking

Magnet

ху

chambers

Absorber


Complex absorber/small angle shield system to minimize background (90 cm from vertex)


Dipole Magnet: bending power 3Tm

Trigger chambers

Muon Forward Tracker (MFT)

- ALICE muon arm : detect muon in forward range -4.0<η<-2.5
- MFT design objectives : Increase pointing accuracy for the muon tracks, in particular at low $P_{\rm T}$
- Implementation: 5-plane silicon telescope in front of the hadron absorber






Expectation & performance of ALICE detector

Parameter	Expected	Achieved
Event vertex resolution with ITS-TPC tracks		
vertex resolution at $dN_{\rm ch}/d\eta = 5$, transverse vertex resolution at $dN_{\rm ch}/d\eta = 25$, transverse	$85~\mu\mathrm{m}$ $35~\mu\mathrm{m}$	$97~\mu\mathrm{m}$ $32~\mu\mathrm{m}$
DCA resolution of ITS-TPC tracks in central Pb-Pb col	llisions	
transverse DCA resolution at $p_{\rm T}=0.3~{\rm GeV}/c$ transverse DCA resolution at $p_{\rm T}=3~{\rm GeV}/c$ transverse DCA resolution at $p_{\rm T}=20~{\rm GeV}/c$	$200~\mu\mathrm{m}$ $30~\mu\mathrm{m}$ $15~\mu\mathrm{m}$	$200~\mu\mathrm{m}$ $30~\mu\mathrm{m}$ $15~\mu\mathrm{m}$
DCA resolution of ITS-TPC tracks in pp collisions (inc	luding vertex resolute	ion)
transverse DCA resolution at $p_{\rm T}=0.2~{\rm GeV}/c$ transverse DCA resolution at $p_{\rm T}=3~{\rm GeV}/c$ transverse DCA resolution at $p_{\rm T}=30~{\rm GeV}/c$	$300~\mu\mathrm{m}$ $50~\mu\mathrm{m}$ $25~\mu\mathrm{m}$	$300~\mu\mathrm{m}$ $45~\mu\mathrm{m}$ $20~\mu\mathrm{m}$
Barrel tracking efficiency in central Pb-Pb collisions		
TPC track finding efficiency at $p_{\rm T}>0.2~{\rm GeV}/c$ TPC track finding efficiency at $p_{\rm T}>1.0~{\rm GeV}/c$ ITS matching efficiency at $p_{\rm T}>0.2~{\rm GeV}/c$	> 78% ^a > 90% ^a > 95%	> 70% > 78% > 92%
$\overline{Barrel\ p_{\mathrm{T}}\ resolution}$		
$\Delta p_{\rm T}/p_{\rm T}$ of TPC tracks at $p_{\rm T}=10~{\rm GeV}/c$ $\Delta p_{\rm T}/p_{\rm T}$ of TPC tracks at $p_{\rm T}=30~{\rm GeV}/c$ $\Delta p_{\rm T}/p_{\rm T}$ of ITS-TPC tracks at $p_{\rm T}=10~{\rm GeV}/c$ $\Delta p_{\rm T}/p_{\rm T}$ of ITS-TPC tracks at $p_{\rm T}=30~{\rm GeV}/c$	$4 extstyle -6\% \ 10 extstyle -15\% \ 1 extstyle -2\% \ 2 extstyle -3\%$	$6\% \\ 18\% \\ 1.5\% \\ 2.5\%$
Barrel particle identification		
TPC dE/dx resolution in pp TPC dE/dx resolution in central Pb-Pb TOF resolution T0 resolution	5.4% $6.8%$ $60-110 ps$ $15-50 ps$	5.2% 6.5% 80 ps 21 ps
Muon spectrometer		
MUON track finding efficiency invariant mass resolution at J/ψ peak in central Pb–Pb invariant mass resolution at Υ peak in central Pb–Pb	95% $70-74 \text{ MeV}/c^2$ $99-115 \text{ MeV}/c^2$	$85-87\% \ 73 { m MeV}/c^2 \ 147(27) { m MeV}/c^2$

A Cosmic Ray Detector for ALICE (ACORDE)



• 20 scintillator modules $(1.88 \times 0.2 \text{ m}^2)$ arranged in a doublet configuration are covering the central part of the top face



